## **PRODUCT FICHE**

Manufacturer		DAIKI
Outdoor unit		RXA42B5V1B9
Indoor unit		FTXA42C2V1BW
Outdoor sound nower level (dB)	$d\mathbf{B}(\mathbf{A})$	62.0
Indoor sound level	dB(A)	60.0
The refrigerant (GWP)		R-32 (675)
Cooling mode		
SEER		7.50
Energy efficiency class		A++
Annual electricity consumption	kWh/a	196
Design load Pdesignc	kW	4.20
Heating mode: Average climate Design temperature = -10°C		
SCOP		4.60
Energy efficiency class		A++
Annual electricity consumption	kWh/a	1156
Design load Pdesignh at -10°C	kW	3.80
Required back up heating capacity at -10°C	kW	0.76
Declared capacity at -10°C	kW	3.04
Heating mode: Warm climate Design temperature = 2°C		
SCOP		5.87
Energy efficiency class		A+++
Annual electricity consumption	kWh/a	489
Design load Pdesignh at 2°C	kW	2.05
Required back up heating capacity at 2°C	kW	0.00
Declared capacity at 2°C	kW	2.05
Heating mode: Cold climate Design temperature = -22°C		
SCOP		
Energy efficiency class		
Annual electricity consumption	kWh/a	
Design load Pdesignh at -22°C	kW	
Required backup heating capacity at -22°C	kW	
Declared capacity at -22°C	kW	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

\*2 Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.