PRODUCT FICHE

Manufacturer		DAIK
Outdoor unit		RXM35A5V1B9
Indoor unit		FTXM35A5V1B
Outdoor sound power level (dB)	dB(A)	58.0
Indoor sound level	dB(A)	58.0
The refrigerant (GWP)		R-32 (675)
Cooling mode		
SEER		9.25
Energy efficiency class		A+++
Annual electricity consumption	kWh/a	132
Design load Pdesignc	kW	3.5
Heating mode: Average climate Design temperature = -10°C		
SCOP		5.2
Energy efficiency class		A+++
Annual electricity consumption	kWh/a	673
Design load Pdesignh at -10°C	kW	2.5
Required back up heating capacity at -10°C	kW	0
Declared capacity at -10°C	kW	2.5
Heating mode: Warm climate Design temperature = 2°C		
SCOP		6.39
Energy efficiency class		A+++
Annual electricity consumption	kWh/a	309
Design load Pdesignh at 2°C	kW	1.41
Required back up heating capacity at 2°C	kW	0
Declared capacity at 2°C	kW	1.41
Heating mode: Cold climate Design temperature = -22°C		
SCOP		
Energy efficiency class		
Annual electricity consumption	kWh/a	
Design load Pdesignh at -22°C	kW	
Required backup heating capacity at -22°C	kW	
Declared capacity at -22°C	kW	

Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 675. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 675 times higher than 1 kg of CO2, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

^{*2} Energy consumption based on standard test results. Actual energy consumption will depend on how the appliance is used and where it is located.